

Fingerprint Door Access & Time Attendance System

One finger solves it all




Model: AC801 / AC802 / AC803 / AC801 WG




[LAYOUT PLAN]

System Communication



Installation Diagram



[SPECIFICATIONS]

Size (mm)	150(L) x 145(H) x 38.5(W)
Identification Time (s)	1.5 sec for 1000 Templates
Enrollment	Up to 10 fingerprints per user
Fingerprint Placement	Allow rotation of finger placement
FAR	< 0.0001%
FRR	< 1%
Transaction Storage	30,000 (AC801), 100,000 (AC802), 120,000 (AC803)
User Capacity	1,000 templates (AC801) / 1,500 templates (AC802) / 2,800 templates (AC803)
Time Zone	50 time zones setting
Communications	RS232, RS485, TCP/IP; Weigand (for AC801 WG model only)
Baud Rate (bps)	9600, 19200, 38400, 57600, 115200
Operating Temperature (°C)	0 - 45
Operating Humidity (%)	20 - 80
Power	12VDC@3A, regulated
Language	English, Chinese Simplified, Chinese Traditional Indonesian and Thai

Authorized Reseller:

FINGERTEC
www.fingertec.com

© 2004-2006 FingerTec Worldwide Ltd. All rights reserved.