

The door doesn't recognize you, Face ID 3 does

FingerTec Face ID 3

Face Recognition System for Door Access



Face ID 3 is FingerTec's advanced face recognition terminal. Building on the facial recognition technology, Face ID 3 uses high quality infrared cameras to scan your facial features and verify your identity. Face ID 3 is designed to cater to the demand for a contactless solution in biometrics recognition, while maintaining its quality performance and high reliability. The slim and stylish design of Face ID 3 is perfect as a door access solution at any office, delivering higher security and a modern look at the same time. Also, stay on top of things when managing Face ID 3 with FingerTec's practical and reliable in-house software.



Contactless Identification

With Face ID 3, all you need is one look, and you're ready to go. Facial recognition makes it easy for you to verify yourself without having to free your hands.



Manage Your Data Easily

Administration is easy with the Ingress software application. Ingress allows you to remotely manage door activity of all connected terminals, while containing time attendance functions for attendance monitoring.



Accurate Verification

Face ID 3 enrolls vivid images of the user and stores them as a large file for a more accurate face verification.



Time Zone Settings

Face ID 3 now has an additional feature of 50 Time Zones for you to control and organize authorized access at your workplace.




Combine Your Verification Methods

Opt for the combination of verification methods to get an added confirmation of identity. A Face + RFID / Password verification leaves almost no room for security breaches!



Multiple Communication Methods

Sync Face ID 3 with a PC using one of the many available connections: TCP/IP, RS232, RS485, USB flash disk or 26-bit Wiegand input-output.



Multi-Verification Methods

You have multiple verification options with Face ID 3. Verify yourself using face, card, or even by password.



Get Your Extra Features Here

Full colour touch screen, short messaging, work codes, photo display after verification. These are among our many additional features that you get to enjoy with Face ID 3.

WEB LINK

Product
<https://product.fingertec.com/userguide.php>


- Quick Start Guide
- Installation Guide
- User Guide
- Video Guide
- Technical Tips

Ingress Software
<https://product.fingertec.com/userguide.php>


LAYOUT PLAN

System Communication

for illustration only



Installation Diagram



SPECIFICATIONS

MODEL	Face ID 3
SURFACE FINISHING	Acrylonitrile butadiene styrene (ABS) & acrylic
TYPE OF SCANNER	High resolution infrared camera
MICROPROCESSOR	800 MHz
MEMORY	256 MB flash memory & 128 MB SDRAM
ALGORITHM	Face BioBridge VX 8.0
PUSH TECHNOLOGY	Yes
DIMENSION (L X W X H), mm	86 x 62 x 218
STORAGE	
Face templates	1500
Cards	10000
Transactions	100000
ENROLLMENT & VERIFICATION	
Methods	Face (1:1, 1:N), card & password
Verification time (sec)	< 2
Face	FAR < 0.01%, FRR < 0.1%
CARD TECHNOLOGY	
RFID: 64-bit, 125kHz	Yes
MIFARE: MFIS50/S70, 13.56MHz	Made to order
HID: HID 1325, 26-bit, 125kHz	Made to order
COMMUNICATIONS	
Method	TCP/IP, RS232, RS485, USB disk (<i>Optional WiFi</i>)
Baud rates	9600, 19200, 38400, 57600, 115200
Wiegand	26-bit input / output
OPERATING ENVIRONMENT	
Temperature (°C)	0 ~ 45
Humidity (%)	20 ~ 80
Power input	DC12V 3A
TIME ATTENDANCE	
Siren	Buit-in (<i>Optional external</i>)
Work codes	Yes
Fast transaction checking	Yes
Receipt printing	Yes (via RS232)
MULTIMEDIA	
Greeting voice	Yes
Display	3.0" 65K color TFT touch screen panel
Photo-ID	Yes
Day light saving timer	Yes
ACCESS CONTROL	
EM lock driving output	DC 12V / relay output
Alarm output	NO
VOICE / DISPLAY LANGUAGE (TERMINAL)	English (Standard), Arabic, Indonesian, Chinese Traditional / Simplified, Cantonese, Vietnamese, Spanish, Portuguese (Portugal), Turkish, Persian. <i>Other languages are available upon request.</i>
SOFTWARE LANGUAGE	English, Arabic, Chinese Traditional / Simplified, Spanish, Thai, Russian, Malay, German & Indonesian



Packaging

Dimension (mm) : 245 (L) x 90 (W) x 225 (H)
 Weight : 1.6 kg

*NOTE: Specifications are subject to change.
 Check <http://product.fingertec.com> for latest product information.*

Authorized Reseller:



timeTec
www.timeteccloud.com
 TimeTec © 2021, All Rights Reserved