



## Life Gets Exciting and Secured wit metrics

# Live Keyless with Soor Access & Time Attendance System













R3 is the latest biometrics door access and time attendance product from FingerTec, which combines modern technologies, great design and amazing functions in one. This machine features an eye-catching 2.4" color LCD and intuitive touch-panel; made robust to stand the wear and tear of everyday use. Multiple methods of verification which include fingerprint and password are available in R3, providing convenience at its best to busy users. The product comes bundled with Ingress, the perfect door access solution that is loaded with great door access features and comprehensive time attendance features, all without additional charges. With R3, life gets more exciting and secured with keyless door access solution for your life's convenience.



#### **Multiple Verification Methods**

From fingerprint to password verification, R3 provides the possibilities. Optimize your security threshold, with fingerprint verification as your primary enrolment form.



## Precise Recognition with Biometrics

R3 utilizes minutiae matching technology that ensures only enrolled users are granted access, eradicating buddy punching scenarios



### Comprehensive Access

Complement your R3 access control terminal with a R2c slave exit reader for a complete door-in and door out experience.



## High Definition Color Display and Touch Panel

Combining vibrance and function in a single stroke, our 2.4" color LCD and touch panel is bound to please in terms of aesthetics and function.



### **Data Management Simplified**

R3 is equipped with TCP/IP connectivity and when that is not available, a USB flash drive is available to transfer transaction logs into your computer.



#### TimeZone Enable

Secure your premise with timezone features by R3, providing you total control in your access needs. R3 has TimeZone, GroupTimeZone and Group Verify features at your disposal.





#### **Built In Alarm**

R3 allows installation of external alarm to your access system to alert you during emergencies and break-ins. Secure your premise with GroupTimeZone and Group Verify functions.



## Free Firmware and Software Updates

Functions and features are constantly evolving through technological research and industrial needs, hence our software and firmware updates for our devices come complimentary.

#### WEB LINK



Quick Start Guide / Installation Guide

? User Guide

Video Guide Technical Tips

Ingress Software http://info.fingertec.com/ingress



#### Packaging

Dimension (mm) : 225 (L) x 72 (W) x 168 (H) Weight : 0.86 kg









#### LAYOUT PLAN

## System Communication for illustration only





|                                     | INDOOR   |
|-------------------------------------|--|
|                                     | SPECIFICATIONS   |
| MODEL                               | R3   |
| SURFACE FINISHING                   | In-mould labelling (IML), poly carbonate (PC) & acrylonitrile butadine systene (ABS  |
| TYPE OF SCANNER                     | Non coated optical scanner   |
| MICROPROCESSOR                      | 400 MHz  |
| MEMORY                              | 256 MB flash memory & 32MB SDRAM   |
| ALGORITHM                           | Biobridge VX 10.0  |
| PUSH TECHNOLOGY                     | Yes  |
| DIMENSION (L X W X H), mm           | 78 x 32 x 190  |
| STORAGE                             |  |
| Fingerprint templates               | 3000   |
| Transactions                        | 100000   |
| ENROLLMENT & VERIFICATION           |  |
| Methods                             | Fingerprint (1:1, 1:N) & password  |
| Recommended fingerprint per user ID | 2  |
| Fingerprint placement               | Any angle  |
| Verification time (sec)             | <1   |
| FAR (%)                             | < 0.001  |
| FRR (%)                             | <1   |
| COMMUNICATIONS                      |  |
| Method                              | TCP/IP, RS232, RS485, USB disk   |
| Baud rates                          | 9600, 19200, 38400, 57600, 115200  |
| Wiegand                             | 26-bit input / output  |
| OPERATING ENVIRONMENT               | The second secon |
| Temperature (°C)                    | 0 ~ 45   |
| Humidity (%)                        | 20 ~ 80  |
| Power input                         | DC 12V 3A  |
| TIME ATTENDANCE                     |  |
| Work codes                          | Yes  |
| MULTIMEDIA                          |  |
| Greeting voice                      | Yes  |
| Display                             | 2.4" 3k color LCD  |
| Photo ID                            | Yes  |
| Short messaging                     | Yes  |
| ACCESS CONTROL                      |  |
| EM-Lock Driving Output              | DC12V 3A / relay output  |
| Alarm output                        | NO/NC  |
| Antipassback                        | Yes  |
| Voice / Display Language (Terminal) | English (Standard), Arabic, Chinese (Simplified/Traditional), Indonesian, Portuguese (Portugal), Spanish.  Other languages are available upon request.   |
| SOFTWARE LANGUAGE                   | English (Standard), Arabic, Bulgarian, Chinese (Simplified/Traditional), French,<br>German, Hindi, Indonesian, Kurdish, Malay, Persian, Portuguese, Russian, Spanish,<br>Thai, Vietnamese  |

NOTE: Specifications are subject to change.



