

The i-TimeTec smart home/office multifunctional gateway can be used as a hub to connect i-TimeTec smart devices. The i-TimeTec Smart Gateway also built in with a surveillance camera to monitor any movement in your premises to enhance security. It supports voice intercom for remote communication via i-TimeTec App, and embedded with motion sensor that can send realtime alarm to alert host.



Built in Zigbee Gateway



Fasy Installation



720P High Resolution



8m Remote night vision



PTZ Control



Panoramic monitoring



Cloud and Local Storage



Voice Intercom



Motion Sensor



Real-time alarm to i-TimeTec app



Send motion detected video clip to app immediately





SPECIFICATIONS	
MODEL	TT-G3-18
SIZE	85*106mm
LENS PARAMETER	100w resolution, 720p lens
INFRARED DISTANCE	< 10m
VOICE INTERCOM	Two way
STORAGE	Support Micro SD card (max 128G), support Epicamera Cloud Storage
INSTALLATION	Wall mount, side mount, ceiling mount
ROTATING ANGLE	Horizontal 0 to 340, vertically 80 upward and 10 downward
WIRELESS COMMUNICATION PROTOCOL	2.4G Zigbee
WIFI PARAMETER	IEEE802.11b, 802.11g, 802.11n (Outdoor < 100m, indoor < 50m, depends on situation)
SMART ALERT	Motion detect
MAX SMART DEVICES TO CONNECT	1 Smart Gateway Camera can connect to maximum 36 devices
© 2020 Timetec Cloud Sdn Bhd. All rights reserved • 022020	