



The latest addition of Face ID series has arrived and this time around the face recognition machine is made bigger and better!

Face ID X is a biometric verification terminal that contains two types of advanced biometrics technologies with dual cameras, 1.2 GHz Single Core microprocessor, 1.0GB flash memory, 1.0GB SDRAM, various types of data communication and an enormous data storage capacity; all of which to provide a swift and accurate biometrics verification. The device can contain up to 30K face recognition with 1:1 verification, 10K fingerprint templates and a huge 1 million transaction data at any given time. Face ID X is designed to provide users with a convenient and contactless verification in addition to multiple verification options. With the mighty capacity in which Face ID X offers, the face recognition machine is thus taken to another level of power!



Contactless Identification
One of the many advantages of
face identification is its
contactless nature. Just stand
still in front of the camera and
get verified instantly.



Multi-Verification Method for Versatility Face ID X offers four different types of identity verifications Fingerprint, Face ID and password.

FINGERTEC



Tighten Security
Face ID X caters to a tighter access control system with implementation of both face & fingerprint biometric authentication methods simultaneously.



No Waiting Time It takes 2 seconds to verify an identity through face recognition and 1 second for fingerprint. It'll be done before you know it!









Security and Accuracy Assured

Face ID X can be installed for door access and staff time & attendance providing companies with security and data accuracy from one single system.



Supersized Capacity
Face ID X can store up to

Face ID X can store up to 30,000 face templates, 10,000 fingerprint templates and up to 1,000,000 transaction logs which can be downloaded into a computer via TCP/IP, RS232, RS485, or via USB flash disk connection.



Shortcut Keys for Convenience

Face ID X presents users with the convenient shortcut keys, programmable for the commonly used functions.



Smooth Navigation
The full colour touch screen in
Face ID X makes it easy for
users to navigate through the
system.

# **WEB LINK**








# Packaging

Dimension (mm) :298 (L) x 123 (W) x 222 (H)


Weight :1.84 kg

# LAYOUT PLAN

# System Communication for illustration only



# Installation Diagram



	SPECIFICATIONS
MODEL	Face ID X
SURFACE FINISHING	Acrylonitrile butadiene styrene (ABS) & acrylic
TYPE OF SCANNER	Hi-res infrared camera & fingerprint scanner
MICROPROCESSOR	1.2GHz Single Core CPU
MEMORY	1.0GB SDRAM/ 1.0GB flash
ALGORITHM	Face BioBridge VX7.0, Fingerprint BioBridge VX9.0 / 10.0
	Yes
PUSH TECHNOLOGY	194 x 110 x 145
DIMENSION (L X W X H), mm	194 X 110 X 145
STORAGE	10,000
Fingerprint templates	10,000
Face templates	3000 (1:N), 30000(1:1)
Transactions	1000000
ENROLLMENT & VERIFICATION	
Methods	Face (1:1, 1:N), fingerprint (1:1, 1:N) & password
Recommended fingerprint per user ID	2
Fingerprint placement	Any angle
Verification time (sec)	Face < 2, Fingerprint < 1
Fingerprint	FAR < 0.0001%, FRR < 0.1%
Face	FAR < 0.01%, FRR < 0.1%
COMMUNICATIONS	
Method	TCP/IP, RS232, RS485, USB disk
Baud rates	9600, 19200, 38400, 57600, 115200
Wiegand	26-bit output
OPERATING ENVIRONMENT	
Temperature (°C)	0 ~ 45
Humidity (%)	20 ~ 80
Power input	DC 12V 3A
TIME ATTENDANCE	·
Siren	Internal and external
Work codes	Yes
Fast transaction checking	Yes
MULTIMEDIA	
Display	4.3" 65K color TFT touch screen panel
Photo-ID	Yes
Short messaging	Yes
Day light saving timer	Yes
	Yes (DC 12V, 2000mAh)
Internal backup battery ACCESS CONTROL	TES (DE 124, 2000HIMH)
	DC 13V / relay output
EM lock driving output	DC 12V / relay output NO/NC
Alarm output	115,115
VOICE / DISPLAY LANGUAGE (TERMINAL)	English (Standard), Arabic, Indonesian, Chinese Traditional / Simplified, Cantonese, Vietnamese, Spanish, Portuguese (Portugal), Turkish, Persian.  Other languages are available upon request.









