



www.fingertec.com

A Firm Access with Kadex Series























Kadex series is an access control and time attendance card reader system suitable for all types of offices that require a card solution with a modern twist. The main reader Kadex supports card ID, a 5-digit password and a combination of both, m-Kadex is a simpler version of Kadex without any LCD screen and keypads, while i-Kadex and k-Kadex are both the slave readers of Kadex series. A combination of either Kadex or m-Kadex with any of the slave readers will make a complete and cost-effective in/out door access system for your premises.



Small, Yet Loaded with Great Capacity

Kadex and m-Kadex can store a whopping total of 30000 users, and 50000 transaction logs.



Value for Money

Mix and match your FingerTec system with m-Kadex to give you more value for your money. Choose Kadex for the main entrance and m-Kadex for other entrances.



Combine Your Verification Methods

Choose a combination of verification methods to secure your workplace i.e. card and password for tighter security.



Manage Your Shift Workers

Kadex and m-Kadex can be programmed with a total of 50 time zones - perfect for companies with shift work.



Manage Your Data Easily

Administration of data is easy with the bundled software, Ingress. With Ingress you can remotely manage all door activities of the connected terminals and get time attendance functions too.



Built-In Alarm

Increase the security at your workplace by installing an external alarm, and be alerted during unexpected scenarios such as break-ins and fire emergencies.





Simple Administrator Management & Enrollment

m-Kadex's simple outlook is complimented with a simple management system. Just swipe your administrator card to enroll, delete, or reset the terminal.



Easy Data Management

Apart from providing a TCP/IP connection for data transfer, Kadex offers a USB data transfer as well.



WEB LINK



Quick Start Guide

/ Installation Guide

? User Guide Video Guide

Technical Tips

Ingress Software http://info.fingertec.com/ingress



 Packaging

 Dimension (mm): 225 (L) x 72 (W) x 168 (H)

 Weight
 : 0.80 kg (Kadex)

 : 0.72 kg (m-Kadex)










LAYOUT PLAN



| Installation Diagram Power cable and door unlock signal | AC110/240V Power Input | AdapTe | | argeable |
|--|---------------------------|------------------------|--------|---------------------------------------|
| Door lock system RS232/RS4 or TCP/II Networked System | | Override Key Switch | INDOOR | Emergency Break Glass Push Button |

| SPECIFICATIONS | | | | | | |
|---|---|---------------------------------|--|--|--|--|
| MODEL | Kadex | m-Kadex | | | | |
| SURFACE FINISHING | Acrylonitrile butadiene styrene (ABS) | Polycarbonate | | | | |
| TYPE OF ANTENNA | RFID | | | | | |
| MICROPROCESSOR | 400 MHz | | | | | |
| MEMORY | 8 MB flash memory & 32 MB SDRAM | 4 MB flash memory & 32 MB SDRAM | | | | |
| PUSH TECHNOLOGY | Yes | N/A | | | | |
| DIMENSION (L X W X H), mm | 92 x 49 x 137 | 92 x 29 x 134 | | | | |
| STORAGE | | | | | | |
| Cards | 30000 | | | | | |
| Transactions | 50000 | | | | | |
| ENROLLMENT & VERIFICATION | | | | | | |
| Methods | Card & password | Card | | | | |
| Card per user ID | 1 | | | | | |
| Reading distance, mm | 40 ~ 80 (RFID, HID), 30 ~ 50 (Mifare) | | | | | |
| Verification time (sec) | <1 | | | | | |
| CARD TECHNOLOGY | | | | | | |
| RFID: 64-bit, 125kHz | Yes | | | | | |
| MIFARE: MFIS50/S70, 13.56MHz | Made to order | | | | | |
| HID: HID 1325, 26-bit, 125kHz | Made to order | | | | | |
| COMMUNICATIONS | | | | | | |
| Method | TCP/IP, RS232, RS485, USB disk | | | | | |
| Baud rates | 9600, 19200, 38400, 57600, 115200 | | | | | |
| Wiegand | 26-bit input / output | | | | | |
| OPERATING ENVIRONMENT | | | | | | |
| Temperature (°C) | 0 ~ 45 | | | | | |
| Humidity (%) | 20 ~ 80 | | | | | |
| Power input | DC 12V 2A | | | | | |
| TIME ATTENDANCE | | | | | | |
| Work codes | Yes | N/A | | | | |
| MULTIMEDIA | | | | | | |
| Voice | Yes | N/A | | | | |
| Display | Black and White | N/A | | | | |
| Short messaging | Yes | N/A | | | | |
| ACCESS CONTROL | | | | | | |
| EM lock driving output | DC 12V 3A / relay output | | | | | |
| Alarm output | NO / NC | | | | | |
| Anti passback | Yes | | | | | |
| VOICE / DISPLAY LANGUAGE (TERMINAL) (only for Kadex) | English (Standard), Arabic, Chinese (Simplified/Traditional), Indonesian, Portuguese (Portugal), Spanish. Other languages are available upon request. | | | | | |
| SOFTWARE LANGUAGE | English (Standard), Arabic, Bulgarian, Chinese (Simplified/Traditional), French, German, Hindi, Indonesian, Kurdish, Malay, Persian, Portuguese, Russian, Spanish, Thai, Vietnamese | | | | | |

*N/A: Not applicable

NOTE: Specifications are subject to change. Check http://product.fingertec.com for latest product information.



