

PIR/MOTION SENSOR HIGH-PERFORMANCE MOTION DETECT CAMERA

i-TimeTec PIR Motion Sensor designed for smart home/office applications. It is mainly composed of an infrared pyrolysis probe and zigbee transmission core piece of composition. It connects to the i-TimeTec intelligent gateway via the zigbee protocol and transmits sensor data over the gateway to the i-TimeTec cloud.

i-TimeTec PIR sensor gains the information when people come or pass by the way through IR. PIR integrates the infrared security and infrared control.



SPECIFICATIONS	
MODEL	TT-W331A-AGI
SIZE	85 x 63 x 48mm
WORKING VOLTAGE	DC3V
QUIESCENT CURRENT	≤ 10uA
WORKING CURRENT	≤ 190mA
WORKING FREQUENCY	2.4GHz
POWER SUPPLY METHOD	Battery (CR123A)
WIRELESS COMMUNICATION PROTOCOL	Zigbee
COMMUNICATION COVERAGE	\leq 15m (without barrier)
DETECTION RANGE	Radius 7m, Angle 90 degree (Room temperature 25 °C)
INSTALLATION	Wall Mount / Double sided adhesive
INSTALLATION HEIGHT	2.2m (recommended)
ALARM GAP	5 min
WORKING ENVIRONMENT	Temperature 10–50 °C / Humidity 5–95%
COLOR	White



