













GPRS Connectivity

Don't want the hassle of wires? Then opt for our GPRS enabled terminals instead. Connect to the PC TO sync data over a GPRS connection without having a range limit.



Workcodes

Let your staff experience more independence by reporting their whereabouts via our workcodes feature.



Eliminate Buddy Punching

The weakness with the clock-in card system is that 'buddy punching' can occur where one employee can clock in the time for another employee if any of them are late. Eliminate this occurrence by using the unique per-individual fingerprint as a clock-in card!



Short Message Display

Alert your staff by personalizing a short message to be displayed at the terminal when they verify.



Manage Your Data Easily

Administration is easy with the bundled software! FingerTec's TCMS software allows you to generate reports, monitor attendance and integrate FingerTec with a third party system



User-Friendly Icons

Complete with configuration icons, the interface in the TA100C couldn't be more user-friendly.



Full Colour Screen

This model comes with a full colour TFT screen. Display pictures corporate advertisements, screen savers and much more on the colour screen of the terminals.



Built-In Alarm

Increase the security at your workplace by installing an external alarm, and be alerted during unexpected scenarios such as break-ins and fire emergencies.

• http://info.fingertec.com/ta100c-1



Quick Start Guide

• http://info.fingertec.com/ta100c-2



/ Installation Guide

• http://info.fingertec.com/ta100c-3



? User Guide

• http://info.fingertec.com/ta100c-4



Video Guide

• http://info.fingertec.com/ta100c-5



Technical Tips

• http://info.fingertec.com/ta100c-6



 Packaging

 Dimension (mm) : 245 (L) x 90 (W) x 225 (H)


 Weight : 1kg





LAYOUT PLAN

Layout Plan



SPECIFICATIONS		
MODEL	TA100C GPRS	TA100CR GPRS
SURFACE FINISHING	Acrylonitrile Butadiene Styrene (ABS)	
TYPE OF SCANNER	Non coated optical scanner	
MICROPROCESSOR	800MHz	
MEMORY	256MB flash memory & 128 MB SDRAM	
ALGORITHM	BioBridge VX 9.0 / BioBridge VX 10.0	
PRODUCT DIMENSION (L X W X H), mm	190 x 52 x 140	
STORAGE		
Fingerprint templates	8000	
Transaction	200000	
ENROLLMENT & VERIFICATION		
• Methods	Fingerprint (1:1, 1:N), Password	Fingerprint (1:1, 1:N), Card & Password
Recommended fingerprint per user ID	2	
Fingerprint placement	Any angle	
Verification time (sec)	<1	
• FAR (%)	< 0.0001	
• FRR (%)	<1	
CARD TECHNOLOGY		
• RFID: 64-bit, 125kHz	N/A	Yes
• MIFARE: MFIS50/S70, 13.56MHz	N/A	Made to order
• HID: HID 1325, 26-bit, 125kHz	N/A	Made to order
COMMUNICATIONS		
• Method	TCP/IP, USB disk & GPRS (Optional: RS232, RS485 & WiFi)	
Baud rates	9600, 19200, 38400, 57600, 115200	
OPERATING ENVIRONMENT		
• Temperature (°C)	0 ~ 45	
• Humidity (%)	20 ~ 80	
Power input	DC5V 2A	
TIME ATTENDANCE		
• Siren	Built-in and external	
• Work codes	Yes	
MULTIMEDIA		
• Voice	Yes	
• Display	3.0" 65k color TFT screen	
Short messaging	Yes	
VOICE / DISPLAY LANGUAGE (TERMINAL)	English (Standard), Arabic, Malay, Indonesian, Chinese Traditional / Simplified, Cantonese, Thai, Vietnamese, Spanish, Portuguese (Portugal), Portuguese (Brazil), French, Russian, German, Turkish, Persian. Other languages are available upon request.	
SOFTWARE LANGUAGE	English, Arabic, Arabic (Kuwait), Chinese Traditional / Simplified, Persian, French, German, Indonesian, Italian, Korean, Lithuanian, Malay, Polish, Portuguese, Portuguese (Brazil), Russian, Spanish, Thai, Turkish, Vietnamese	

*N/A: Not applicable

NOTE: Specifications are subject to change. Check http://product.fingertec.com for latest product information.

Authorized Reseller:



©2015 Timetec Computing Sdn Bhd. All rights reserved.